

## FEATURES

- Rugged compressor with cast iron cylinders
- "V" design minimizes vibration, improves cooling and extends compressor life
- Individual and removable cylinders for smoother and cooler operation
- Heavy duty pressure switch has on/off control
- Thermally protected electric motors, CSA/US approved
- Metal air filters with "Auto Drop" feature
- Convenient oil drain on front of unit
- 25 gallon ASME registered tank, 150 PSIG rating
- Steel rim pneumatic tire for easy handling and maneuverability
- Easy view oil sight gauge
- High efficiency reed valves for maximum performance
- Efficient heat removal from pulley-fan for cooler running and longer life
- Sturdy metal belt guard
- Outlet valve and regulator included

### P3125H1-DV

**6.0  
CFM**  
@ 100 PSI

**Dual  
Control  
Dual  
Voltage  
110/220**



### P4125H1

**12.5  
CFM**  
@ 100 PSI

**Dual  
Control  
208/230**



### P5125H1

**18.5  
CFM**  
@ 100 PSI



MODEL	HP	CFM@ 100 PSI	MAXIMUM RATED PSI	RECEIVER CAPACITY	MOTOR	DIMENSIONS L-W-H (ins)	WEIGHT (lbs)
P3125H1-DV	3.0	6.0	150	25 Gal	208/230V	44-18-30	200
P4125H1	5.0	12.5	150	25 Gal	208/230V	44-18-30	200
P5125H1	5.0	18.5	150	25 Gal	208/230V	44-18-33	250

Toll Free 1-800-551-2406 Ext. 295

[www.eaglecompressor.com](http://www.eaglecompressor.com)